



# SOILMIXER

The soilmixer is developed to mix and sprinkle every kind of soil.

## OPERATION:

The material which has to be mixed will be brought into the soilmixer by hand or by means of a conveyor-belt. After feeding in the mixture or mixtures the drum will be closed on the input- and output sides, eventually water can be dosed.

The mixing will be started and after the desirable mixing-time the drum will be opened on the outputside and the mixture can be dosed for example into a handlingmachine. The drum is supplied with mixer-blades for an intensive and optimal mixing result.

## THE MACHINE HAS FOLLOWING DISTINGUISHING FEATURES:

- High-quality construction and maintenance free
- High mix-efficiency
- 2 models, 2.500 en 4.000 litre gross drumcapacity, nett drumcapacity respectively 2.000 and 3.000 litre
- Available for many mixtures
- Easy operation
- Movable construction
- Built in accordance with the CE-norm

## OPTIONS:

- Supply-funnel



## TECHNICAL DATA:

Length	: 3.000 mm.
Width	: 2.500 litre mixer 1.450 mm.
Width	: 4.000 litre mixer 1.800 mm.
Height	: 2.000 mm.
Weight	: ± 1.000 kg.
Connection power	: 2.500 litre mixer: 2,2 kW
Connection power	: 4.000 litre mixer: 4,4 kW
Power supply	: 3ph./400V.50Hz. + N + ⚡

