



LABELDISPENSER TYPE BRU 75

The labeldispenser is developed to apply self-adhesive labels to flowerpots.

OPERATION:

The roll of labels is placed on the rollholder, the labeling track goes via a tension pulley and a forksensor to the dispensertongue, this dispensertongue applies the labels at the set height to the pot, and the label is pressed on more securely by a brush on a catch spring. The bottom layer of the labels is automatically rolled up while the labels are being dosed by means of a winder with a pressure roller. The labelposition is determined by such factors as a pot recognition sensor that transmits a signal to the labeldispenser during recognition. In addition each format of label is automatically calibrated by the forksensor.

THE MACHINE HAS THE FOLLOWING DISTINGUISHING FEATURES:

- Stand-alone machine
- Top-quality construction and low maintenance
- High capacity to 4.500 labels per hour
- Frame is adjustable in height for every application
- Movable equipped with two brake wheels
- Suitable for large and small orders
- Adjustable for virtually every labelsize
- Suitable for all conveyorbelts
- Labeling possible at potting or delivery
- Easy operation, manually adjustable
- Built in accordance with the CE-norm



TECHNICAL DATA:

Length	: 590 mm.
Width	: 420 mm.
Height	: 1.350 mm
Weight	: 30 kg.
Labeling speed	: till 15 meter per minute
Capacity	: till max. 4.500 per hour (depending on label)
Label height	: max 75 mm.
Label length	: 25 – 200 mm.
Label roll diameter	: maximally 220 mm.
Core diameter	: minimally 45 mm.
Power supply	: 230V. 50Hz.

